



BAUSER®

Battery Monitors Type 827 "Non Starting batteries"



Battery Monitor [with relay]

Battery Type	Most lead acid & gel batteries
Operating Voltages	12, 24, 36 or 48 VDC
Display	8 LED's (7 yellow, 1red)
Discharge Voltages	Fixed 1.73 V/cell
Pre warning	25% capacity the last yellow LED flashes
Relay output / lockout	Yes 20% (12-24 VDC / 2A, 36 VDC / 1.5A, 48 VDC / 1A)
Vibration resistance	20g SAEj1378, 1g EN60068-2-34Continuous Shock
Shock resistance	EN600/68-2-27 (30g, 18 msec) Continuous Shock EN600/68-2-29 (25g, 6 msec)
EMC	EN55011; EN 61000-6-Z
Protection (front)	IP 65 (front)
Fixing	Retaining clip

Stock Items: (for pricing see page 5 of Item Price List)

TYPE	Description	Relay	Part No.
827	Round case 52 mm diameter, 12 VDC	YES	5 827 012
827	Round case 52 mm diameter, 24 VDC	YES	5 827 024
827	Round case 52 mm diameter, 36 VDC	YES	5 827 036
827	Round case 52 mm diameter, 48 VDC	YES	5 827 048

OPTIONS:

Spacer sleeve to convert 52mm gauges to 60mm gauges. Fits all 52 mm gauges.	5 000 001
Independent rubber mounting to dampen excessive vibration (requires spacer).	5 000 110