

## Screw type Contacts

### ET and M series



### ET Series Contacts

Approvals	CE, CSA, GOST-R, UL
Protection Class	II (protective insulation)
Mechanical and Electrical life	1 million cycles (at rated load)
Operating temperatures	-30 to 55...70 deg C (depending on illumination)
Contact Rating (IEC/EN 60947-5-1)	250V/5A (AC15) / 60V/1A (DC13)
Lamps	BA9s base max 250V/2W (CSA max 150V)
Continuous Thermal Load	10A
Min Load	5V/1mA (under laboratory conditions)

**Stocked Items:** (for pricing see page 9 of Item Price List)

Part Number	Description
ETR	1 x Normally Open and 1 x Normally Closed Contacts
ETR2	2 x Normally Open and 2 x Normally Closed Contacts
ETLR	Incandescent globe base (BA9s), 1 x Normally Open and 1 x Normally Closed Contacts
ETLR2	Incandescent globe base (BA9s), 2 x Normally Open and 2 x Normally Closed Contacts
ET9R	Incandescent globe base (BA9s)



### M Series Contacts

Approvals	CE, CSA, GOST-R, UL, KEEMA, CCC
Protection Class	II (protective insulation)
Mechanical and Electrical life	1 million cycles (at rated load)
Operating temperatures	-30 to 55...85 deg C (depending on illumination)
Contact Rating (IEC/EN 60947-5-1)	250V/3A (AC15) / 60V/1A (DC13)
Lamps	BA9s base max 250V/2W (CSA max 150V)
Continuous Thermal Load	16A
Minimum Load	5V/1mA (under laboratory conditions)

**Stocked items:** (for pricing see page 11 of Item Price List)

Part Number	Description
MHR_3	Housing suit individual contacts (3 pieces)
MHR_5	Housing suit individual contacts (5 pieces)
MTI	Momentary, single Normally Open contact
MTO	Momentary, single Normally Closed contact
MTOSFE	Safety contact ( <b>SELF MONITORING</b> ), single Normally Closed contact
ML	Lamp Module suit BA9s
MFL	Latching module with globe holder suit BA9s
MAL	Connection module suit Illuminated Estops, 12-30 VAC/DC, max 44 mA
MLED12-120...	LED Lamp module, 12-120 VAC/DC, B = Blue, G = Green, R = Red, Y = Yellow, W = White
MFLED24...	LED Lamp module 24VAC/DC, Latching, B = Blue, G = Green, R = Red, Y = Yellow, W = White

All prices exclude GST. We reserve the right to change technical specifications & prices without prior notice.