

Pressure Gauges

40mm All Stainless Steel



Model RCh(G)

Body Material	304 Stainless Steel Case
Ranges	-100 and up to 100,000 kPa
Conforms to	Australian Standard AS1349 or better
Wetted parts	316L stainless steel
Lens	Polycarbonate
Protection	IP54 dry / IP65 liquid filled
Accuracy Class	40mm 1.6 % Full scale deflection
Connection	Centre Rear entry 1/8 NPT



Stocked Product Ranges: (for pricing see page 3 of Item Price List)

Dial Size	40 mm (1 1/2")		
Range ↓		Range ↓	
0... 100 kPa	6 342 418	0... 6000 kPa	6 342 429
0... 160 kPa	6 342 419	0...10000 kPa	6 342 430
0... 250 kPa	6 342 420	0...16000 kPa	6 342 431
0... 400 kPa	6 342 421	0...25000 kPa	6 342 432
0... 600 kPa	6 342 422	0...40000 kPa	6 342 434
0... 800 kPa	6 342 423	0...60000 kPa	6 342 435
0... 1000 kPa	6 342 424		
0... 1600 kPa	6 342 426		
0... 2500 kPa	6 342 427		
0... 4000 kPa	6 342 428		
Stock Options			
Liquid filling	99 100 100	(pricing shown IPL page 19)	99 100 100
Panel Mount Assy	6 342 002		6 0342 002

Special Manufacture: (delivery times apply)

- Custom dials
- Other mounting options
- Other threads
- Switch contacts
- Rear entry and bottom entry for 40mm, 50mm, 63mm and 100 mm gauges

All prices exclude GST. We reserve the right to change technical specifications & prices without prior notice.