



Model PsPK63 - 2

Body Material	63 mm Glass Reinforced Polyamide Screw Ring Case
Ranges	-100 and up to 4000 kPa
Wetted parts	Carbon Steel with silver coated diaphragm
Lens	Instrument Glass
Protection	IP65
Accuracy Class	Full scale deflection
Thread	1/4 BSP tapered

Designed for use with
Chlorine



Stock Ranges: (for pricing see page 4 of Item Price List)

Range	Connection	Part Number
To Be Specified on Order	Rear or bottom	PsPK63-2

Model DRg...Fz

Body Material	60 mm Steel case (panel mount via U bracket)
Ranges	0 to either 600, 1000 or 1200 kPa
Illumination	BA9s (Max 24vdc / 2 watts)
Wetted parts	2 x Independent Brass / Bronze assemblies
Lens	Instrument Glass
Protection	IP54 front
Accuracy Class	1.6 % Full scale deflection
Thread	2 x M12 x 1.5 with cone suit L6 hose

Dual Air Pressure



Stock Ranges: (for pricing see page 4 of Item Price List)

Range	Connection	Part Number
0 to 12 Bar	Rear	DRg60-1FZ rmBfr 0-12

Special Manufacture: (delivery times apply)

- Other pressure ranges
- Custom dials
- Other mounting options
- Other threads
- Switch contacts
- Rear entry and bottom entry for 40mm, 50mm, 63mm and 100 mm gauges

All prices exclude GST. We reserve the right to change technical specifications & prices without prior notice.