


B Series Contacts (3 mm travel)

Approvals	CE, CSA, GOST-R, UL, KEEMA, CCC
Protection Class	II (protective insulation)
Mechanical and Electrical life	1 million cycles (at rated load)
Operating temperatures	-50 to 55...70 deg C (depending on illumination)
Contact Rating (IEC/EN 60947-5-1)	250V/3A (AC15) / 60V/1A (DC13)
Lamps	BA9s base max 250V/2W (CSA max 150V)
Continuous Thermal Load	6A
Minimum Load	5V/1mA (under laboratory conditions)



(for pricing see page 7, 8, 9, 10 and 15 of Item Price List)

Contacts suit push button actuators:

Part Number	Description
BT	Momentary, 1 x Normally Open and 1 x Normally Closed Contacts
BT_439	Momentary, 2 x Normally Open and 2 x Normally Closed Contacts
BTL	Illuminated (W2x4.6d), momentary, 1 x Normally Open and 1 x Normally Closed Contacts
BTL_439	Illuminated (W2x4.6d), momentary, 2 x Normally Open and 2 x Normally Closed Contacts
BF	Maintained, 1 x Normally Open and 1 x Normally Closed Contacts
BF_439	Maintained, 2 x Normally Open and 2 x Normally Closed Contacts
BFL	Illuminated (W2x4.6d), maintained, 1 x Normally Open and 1 x Normally Closed Contacts
BFL_439	Illuminated (W2x4.6d), maintained, 2 x Normally Open and 2 x Normally Closed Contacts
BL4	Lamp holder, W2x4.6d
L2x4,6-12U...	W2x4,6 LED, 12VAC/DC (7/14mA), B = Blue, G = Green, R = Red, Y = Yellow, W = White
L2x4,6-24U...	W2x4,6 LED, 12VAC/DC (7/14mA), B = Blue, G = Green, R = Red, Y = Yellow, W = White
W2x4,6-12V	W2x4,6 globe, 12V 1.2W
W2x4,6-24	W2x4,6 globe, 30V 1.2W
XA	Connector to suit faston terminals (all A / B Series contacts)
FH2,8	Faston terminal 2.8 x 0.8mm

The above listing is for stocked items only, please contact us for the complete manufacturers listing if the product you are looking for is not listed above.

All prices exclude GST. We reserve the right to change technical specifications & prices without prior notice.