



For continuous level measurement in tanks containing fuel oil EL, diesel fuel, biodiesel or water. These are odour tight and therefore very suitable for flood prone areas

### Mechanical Level Sensing

Body Material	ABS
Connection	G 1 1/2
Float	PE-HD
Tank Depth	MT Profil R (0 to 150 cm or 250 cm) Unimes (90 to 200 cm)



For use with liquid mediums with low viscosity which do not attack PE-HD

**Stocked Options:** (for pricing see price list page 1)

Part Number	Description
11500	Unimes - Mechanical Level indicator, 0-100 %, with reference pointer
16500	MT Profil R - Mechanical level indicator , ABS body, reversible scale, odour proof, Float PE-HD
<b>OPTIONS:</b>	
20903	2 " thread adaptor to suit MT Profil R

### Pneumatic Level Sensing

Body Material	ABS
Connection	G 1 1/2
Accuracy	+/- 2 % of full scale
Mediums	Fuel oil or Diesel fuel (density = 0.84 g/cm <sup>3</sup> )
Zero Correction	Located on front side
Remote Indication	Up to maximum of 50 metres
Tank Depth	90 to 300 cm (others upon request)



**Stocked Options:** (for pricing see price list page 1)

Part Number	Description
28000	Unitop 3000 - Pneumatic Level Indicator
20153	Pneumofix - Installation kit for Pneumatic level indicators

All prices exclude GST. We reserve the right to change technical specifications & prices without prior notice.