



Model RF63 / RF80 — OGF

Case Material	304 Stainless Steel Case
Ranges	-100 and up to 60,000 kPa (dual scale / PSI)
Conforms to	Australian Standard AS1349 or better
Wetted parts	Brass / bronze
Medium temperature	-20 to 60°C
Lens	Polycarbonate
Protection	IP54 (above 2500 kPa IP65)
Accuracy Class	1.6 % Full scale deflection

Refer to page 63 for line drawings

Dial Size	63 mm (2")		80 mm (2 1/2")
Mounting	bottom	rear	rear
Thread Size	1/4" NPT	1/4" NPT	1/4" NPT
Range ↓	(for pricing see pages 4 of Item Price List)		
-100... 0 kPa	6 161 403 OGF		
0... 160 kPa		6 162 419 OGF	6 182 419 OGF
0... 250 kPa		6 162 420 OGF	6 182 420 OGF
0... 400 kPa		6 162 421 OGF	6 182 421 OGF
0... 600 kPa	6 161 422 OGF	6 162 422 OGF	6 182 422 OGF
0... 1,000 kPa		6 162 424 OGF	6 182 424 OGF
0... 1,600 kPa		6 162 426 OGF	6 182 426 OGF
0... 2,500 kPa	6 161 427 OGF	6 162 427 OGF	6 182 427 OGF
0... 4,000 kPa		6 162 428 OGF	6 182 428 OGF
0... 6,000 kPa			6 182 429 OGF

Options Model RF — OGF

(for pricing see page 5 of Item Price List)

Rest_BB	Restrictor suit up to and incl 80mm Brass Wetted 0.7mm inner
99 100 100	Surcharge for Glycerine filling for 40mm, 50mm and 63mm gauges
99 100 200	Surcharge for Glycerine filling for 80mm gauges
RF63_FF	RF63 Front Flange (press fit), 3 hole, Stainless Steel
RF63_UC1	Flat bar panel mounting clamp with screws suit RF63,D911
RF63_UC2	NG 63 U clamp, ES 1.43021 with 2 M4 bolts (Heavy Duty)
RF63_SG	RF63 Safety Glass and Seal fitted to Afriso PG63 pressure gauge.
RF63_RBB	Rubber Boot suit 63mm pressure gauges in BLUE
RF63_RBR	Rubber Boot suit 63mm pressure gauges in RED